

GNS-INTEGRATED

ENGINEERED TO BE BETTER

MAINS/BATTERY POWER SENSOR TAP - DECK MOUNTED



Australian designed and manufactured *Autoflo Integrated Goose-Neck Sensor Tap* is suitable for a range of hand-washing applications, particularly in public commercial areas that experience high traffic and therefore high usage, meaning conservation of water is of paramount importance. The 6-star WELS rating ensures hygienic bathroom environments for users, deivered economically and in an environmentally sensitive fashion.

The robust construction, sleek design is complemented by a range of features ensuring consistent performance. The ability to self-range to its environment, the hygienic self-flush performed every 24-72 hours are just some of what sets the *Autoflo Integrated Sensor Tap* apart from other visually similar taps on the market.

CHROME



Mains 100-5156 Battery 100-5162

BRUSHED NICKEL



Mains 100-5157 Battery 100-5163


FEATURES

- Pre-programmed adjustable range
- Operation 240V mains or 6V battery
- Long battery life of 3-4 years
- Self-flushing every 24-72 hours
- Simple installation
- Dual stage water filter
- Suitable for high end applications

SPECIFICATIONS

- TAP BODY Solid brass, plated
- SENSOR OPERATION IR Sensor
- SENSOR RANGE 140mm factory set
- OPERATING SUPPLY Mains or Battery
- OPERATING PRESSURE 150 to 500kPa
- FLOW RATING 4.5 L/min WELS 6 Star
- SOLENOID Latching / soft-closing
- MAX TEMPERATURE 50°C
- Suitable for tempered water

DIMENSIONS







Every effort is made to ensure specifications are correct at the time of printing. Autoflo Pty Ltd reserves the right to make changes without prior notice. All measurements shown are in millimetres.